

Profilrohre : geschweißte Vierkantrohre

nach europäischen Standards / Toleranzen: EN10305-5

in Herstellungslängen von 6 m

Werkstoffe: 4301, 4404, 4571

Zwischenabmessungen und andere Werkstoffe auf Anfrage



Edelstahl Lager Wittwer GmbH

Abmessung (mm)	Abmessung (mm)	Wandstärke (mm)	Gewicht (kg/m)
10	x 10	1,0	0,294
15	x 15	1,0	0,453
15	x 15	1,5	0,661
16	x 16	1,5	0,709
20	x 20	1,5	0,901
20	x 20	2,0	1,176
25	x 25	1,2	0,921
25	x 25	1,5	1,140
25	x 25	2,0	1,495
25	x 25	3,0	2,167
30	x 30	1,2	1,112
30	x 30	1,5	1,379
30	x 30	2,0	1,814
30	x 30	3,0	2,645
35	x 35	1,2	1,304
35	x 35	1,5	1,618
35	x 35	2,0	2,133
35	x 35	3,0	3,124
40	x 40	1,0	1,251
40	x 40	1,2	1,495
40	x 40	1,5	1,858
40	x 40	2,0	2,452
40	x 40	2,5	3,033
40	x 40	3,0	3,602
40	x 40	4,0	4,703
45	x 45	2,0	2,771
45	x 45	3,0	4,169
50	x 50	1,5	2,336
50	x 50	2,0	3,090
50	x 50	3,0	4,559
50	x 50	4,0	5,979
50	x 50	5,0	7,349
60	x 60	1,5	2,814
60	x 60	2,0	3,728
60	x 60	3,0	5,516
60	x 60	4,0	7,255
60	x 60	5,0	8,943

Abmessung (mm)	Abmessung (mm)	Wandstärke (mm)	Gewicht (kg/m)
70	x 70	2,0	4,366
70	x 70	3,0	6,473
70	x 70	4,0	8,531
70	x 70	5,0	10,538
80	x 80	2,0	5,004
80	x 80	3,0	7,430
80	x 80	4,0	9,807
80	x 80	5,0	12,133
80	x 80	6,0	14,724
90	x 90	3,0	8,564
100	x 100	2,0	6,279
100	x 100	3,0	9,344
100	x 100	4,0	12,359
100	x 100	5,0	15,323
100	x 100	6,0	18,630
100	x 100	8,0	23,916
120	x 120	2,0	7,712
120	x 120	3,0	11,493
120	x 120	4,0	15,224
120	x 120	5,0	18,905
120	x 120	6,0	22,563
120	x 120	8,0	29,020
150	x 150	3,0	14,423
150	x 150	4,0	18,738
150	x 150	5,0	23,298
150	x 150	6,0	27,807
150	x 150	8,0	36,675
200	x 200	3,0	18,913
200	x 200	4,0	25,118
200	x 200	5,0	31,272
200	x 200	6,0	37,376
200	x 200	8,0	49,434